

Container Specifications

Size	Internal Dimensions mm feet/inches						Weight kg/lb			
Feet/Inches										
				Length between						
Flat Racks	Length	Width	Height	Headers	Corner posts angle	Max Width	Max Gross	Tare	Payload	
20 fixed-corner	5.935	2.398	2.327	5.935	5.693	2.106	24,000	2,560	21,440	
20' x 8' x 8'6"	19'5 5/8"	7'10 3/8"	7'7 9/16"	19'5 5/8"	18'8 1/8"	6'10 7/8"	52,911	5,644	47,267	
20 collapsible	5.966	2.418	2.286	5.85	5.422	2.058	30,480	2,970	27,510	
20' x 8' x 8'6"	19'6 13/16"	7' 11 13/16"	7'6"	19'2 5/16"	17'9 7/16"	6'9"	67,194	6,547	60,647	
40 fixed-corner	12.08	2.438	2.103	12.08	11.796	2.114	30,480	5,480	25,000	
40' x 8' x 8'6"	39'7 9/16"	8'	6'10 13/16"	39'7 9/16"	38'8 3/8"	6'11 3/16"	67,197	12,081	55,116	
40 open-end	12.192	2.23	1.986	11.9	11.71	2.178	45,000	4,500	40,500	
40' x 8' x 8'6"	40'	7'3 3/4"	6'6 3/8"	39' 1/2"	38'5"	7'1 11/16"	99,208	9,921	89,287	
40 flush-fold	12.178	2.365	1.943	12.058	11.662	2.224	45,000	5,200	39,800	
40' x 8' x 8'6"	39'11 7/16"	7'9 1/16"	6'4 7/16"	39'6 11/16"	38'3 1/8"	7'3 1/2"	99,208	11,464	87,744	

Size										
Feet/Inches										
Open-Tops	Length	Width	Height	Width	Height	Length	Width	Max Gross	Tare	Max Payload
20 open-top	5.919	2.34	2.286	2.338	2.273	5.488	2.23	30,480	2,250	28,230
20' x 8' x 8'6"	19'3 15/16"	7'8 5/16"	7'8 9/16"	7'8"	7' 5 1/2"	18' 1/16"	7' 3 3/4"	67,194	4,960	62,234
40 open-top	12.029	2.348	2.359	2.338	2.275	11.622	2.188	32,500	3,800	28,700
40' x 8' x 9'6"	39' 5 9/16"	7'8 3/8"	7'8 13/16"	7'8"	7'5 9/16"	38' 1 1/2"	7' 2 1/8"	71,650	8,378	63,273

Size Feet/Inches	Door Openings mm feet/inches		Internal Dimensions mm feet/inches			Weight kg/lb			Volume m3 cubic feet Capacity
Dry	Width	Height	Length	Width	Height	Max Gross	Tare	Max. Payload	
20 Standard	2,340	2,274	5,896	2,350	2,393	30,480	2,280	28,200	33
20' x 8' x 8'6"	7' 8 1/16"	7' 5 1/2"	19' 4 1/16"	7' 8 1/2"	7' 9 7/8"	67,200	5,030	62,170	1,179
40 Standard	2,340	2,274	12,032	2,350	2,393	32,500	3,700	28,800	67
40' x 8' x 8'6"	7' 8 1/16"	7' 5 1/2"	39' 5 13/16"	7' 8 1/2"	7' 10 3/16"	71,650	8,157	63,493	2,390
40 High	2,340	2,577	12,032	2,350	2,697	32,500	3,880	28,620	76
40' x 8' x 9'6"	7' 8 1/16"	8' 5 7/16"	39' 5 13/16"	7' 8 1/2"	8' 10 3/16"	71,650	8,550	63,100	2,700
45 High	2,340	2,585	13,556	2,352	2,697	32,500	4,900	27,600	86
40' x 8' x 9'6"	7' 8 3/8"	8' 5 3/4"	44' 5 11/16"	7' 8 9/16"	8' 10 3/16"	71,650	10,800	60,850	3,040

Built Different

Size	Door Openings mm								Volume m3 cubic feet Capacity to
	Width	Height	Length	Width	Height to load line	Max Gross	Tare	Max. Payload	
20 Standard	2,290	2,212	5,451	2,290	2,167	30,480	2,990	27,490	27
20' x 8' x 8'6"	7' 6 1/8"	7' 3 1/16"	17' 10 9/16"	7' 6 1/8"	7' 1 1/4"	67,194	6,591	60,603	995
40 High	2,276	2,471	11,578	2,280	2,425	34,000	4,400	29,600	64
40' x 8' x 9'6"	7' 5 9/16"	8' 1 1/4"	37' 11 13/16"	7' 5 3/4"	7' 11 11/16"	74,957	9,700	65,257	2,250

Built Different